

Copper / PEX Braising Tail

Scope of Use / Specification Sheet

SharkBite® plumbing fittings and pipe are manufactured in Australia at RWC’s state of the art facilities. Stringent quality control and advanced manufacturing procedures guarantee product satisfaction.

SharkBite® is an advanced design push-to-connect plumbing system for potable water distribution. SharkBite® is available in an assortment of over 200 fittings and PEX pipe ranging from 16-25mm size. SharkBite® has been engineered with ease of use and disconnection in mind and while being the most dependable way to join copper and PEX Pipe in any combination – with no soldering, clamps, unions or glue.



F600X

Features and Benefits

- Quick and easy to install in both wet or dry conditions
- No expensive tools required - supplied ready for installation
- Approved for behind the wall application
- Approved for underground installation with SharkBite® Silicone Wrap (F708)
- Instant push-to-connect connection. Cut. Push. Done.
- Removable after installation
- Integral tube liner for PEX installations means no loose components and ensures a secure reliable connection

Materials

Sharkbite® push-to-connect (PTC) fittings are made from LF DZR Brass and are available in 200+ configurations including Couplings, Elbows, Tees, Reducers, Threaded Adaptors, Caps, Breeches, Ball Valves, Tempering Valves and Copping Slip Repair Couplings plus Conversion Couplings and Tees to Cu, SDR7.4 PEX, other SDR9 PEX and PB.

All Sharkbite® PEX Fittings come with a pre-installed tube liner. It is an AS/NZS 3500 requirement when using Push-To-Connect fittings on PEX pipe. Tube liners are not required on copper fittings.

Product List

Order Code	Description
F600X	DN15 CU x 16mm OD Tail
F606X	DN20 CU x 20mm OD Tail

25 YEAR
GUARANTEE

All SharkBite® fittings are guaranteed against defects in materials or manufacturing for a period of 25 years from the date of purchase.

Copper / PEX Braising Tail

Installation

Installation is subject to the requirements of the applicable regulatory authority, the National Construction Code Volume Three – Plumbing Code of Australia, associated reference standards as applicable at the time and AS/NZS 3500. This product is compliant to the Lead Free requirements of the National Construction Code Volume Three. For further Scope of Use, please visit www.rmc.com.au/resources.

Warranty

Reliance Worldwide Corporation (Aust.) Pty. Ltd. (RWC) will either replace or repair any defective goods where the defect arose as a result of manufacture within the warranty period. You may contact RWC at the phone number, address or e-mail shown below for further information or to make a claim.

Visit www.rmc.com.au/warranty to view the warranty statement in full and for further important information.

Standards and Approvals



AS/NZS 2537.2
WMKA 02056

Product Dimensions

Code	End Size 1	2	Weight	L	M
F600X	16mm OD Tail	½" CU	32 g	45	34
F606X	20mm OD Tail	¾" CU	54 g	55	39

Note: All measurements in mm unless otherwise stated.

